

3/4/1

FN- DIALOG(R)File 347:JAPIO|
CZ- (c) 1999 JPO & JAPIO. All rts. reserv.|
TI- VIBRATION ISOLATING DEVICE
PN- 63-308242 A-
PD- December 15, 1988 (19881215)
AU- OKAZAKI TOSHIKAZU; DAIMARU SHIGENORI
PA- TOKAI RUBBER IND LTD [352400] (A Japanese Company or Corporation), JP
(Japan)
AN- 62-144355 -JP 87144355-
AD- June 10, 1987 (19870610)
IC- -4- F16F-013/00; G10K-011/16
CL- 22.2 (MACHINERY -- Mechanism & Transmission); 42.5 (ELECTRONICS --
Equipment)
SO- Section: M, Section No. 812, Vol. 13, No. 148, Pg. 17, April 11, 1989
(19890411)
AB- PURPOSE: To develop an excellent attenuation characteristic, and to
provide with a high vibration isolation performance in which the
temperature dependency of the attenuation characteristic has been
improved, and further to simplify the structure, by mixing, in a
viscous fluid, at least a kind of resin whose glass- transition
temperature is within the range of working temperatures.

CONSTITUTION: Both ends of a cylindrical rubber body 2 are closed
with fittings 4 and 6 to fill a prescribed viscous fluid 8 in the
closed fluid housing space, and a prescribed resin 10 whose
glass-transition temperature is within the range of working
temperatures is mixed in the viscous fluid. Thus, an excellent
attenuation characteristic can be developed, and a high vibration
isolation performance in which the temperature dependency of the
attenuation characteristic has been improved can be provided. Since
the vibration attenuation performance can be improved only by mixing
a prescribed resin, it is not necessary to provide a special
mechanism. Accordingly, it is possible to simplify the structure as a
vibration isolation system, enabling it to be applicable to even
small size products, and further enabling the manufacturing man-hour
and the number of parts to be reduced and an inexpensive system to be
constituted.